


	<b>Shaanxi Automobile Heavy Duty Truck Delong L3000 Lightweight Elite Edition 300 HP 8X4 5.8m Dump Truck (SX3319LB276)</b> <a href="#">+ contrast</a> 
Drive type:	8X4
Wheelbase:	1950+2525+1400mm
engine:	Weichai WP7H300E68
Gearbox:	Fast S10MOQ
Rear axle ratio:	5.286
Body length:	8.715 m
Body width:	2.55 m
Ride height:	3.5 m
Front track:	2011/2011mm
Rear track:	1860/1860mm
Vehicle weight:	11.3 tons
Rated load:	19.57 tons
Total mass:	31 tons
Tonnage level:	Heavy Truck
Approach Angle:	19 degrees
Departure angle:	23 degrees
Origin:	Xi'an, Shaanxi
Market Segments:	Road transport
Remark:	Optional: Electric flip, Tianxing Jianzhixing version (with reversing image), 11R22.5 tubeless tires, extended tool kit (passenger ashtray, cab side wall decals, jack, crowbar, vehicle tool kit), lightweight package (11t 390 single-stage maintenance-free drive axle, 1 1R22.5 tubeless tires + lightweight rims, maintenance-free disconnect balance shaft).
Version:	Lightweight Elite Edition
Fuel Type:	diesel fuel
<b>Engine parameters</b>	
Engine Model:	Weichai WP7H300E68
Engine Brand:	Weichai
Number of cylinders:	6 cylinders
Fuel Type:	diesel fuel
Displacement:	6.8L
Emission standards:	National VI
Maximum horsepower:	300 hp
Maximum output power:	221kW
<b>Cargo box parameters</b>	
Length of cargo box:	5.8 m
Cargo box width:	2.35 m
Cargo box height:	1.5 m
Cargo box form:	Self-unloading
<b>Cab parameters</b>	
Cab:	L3000 Cab
Number of passengers allowed:	2 people
Driver's seat type:	Airbag shock absorbing seat
<b>Gearbox parameters</b>	
Gearbox Model:	Fast S10MOQ
Gearbox brand:	Fast
Forward gears:	10 levels
Reverse gear number:	2
<b>tank</b>	
Fuel tank material:	Aluminum Alloy
Fuel tank capacity:	300L
<b>Chassis parameters</b>	
Frame size:	850×270(single 10)mm
Front axle description:	Drum front axle
Permissible load on front axle:	6500/6500kg
Rear Axle Description:	Maintenance-free drum drive axle
Permissible load on rear axle:	18000(two-axle group)kg
Speed ratio:	5.286
Suspension type (front/rear):	Less leaf spring + two riding bolts + disconnect balance shaft
Number of springs:	3/3/5
<b>tire</b>	
Tire specifications:	11R22.5 16PR,11R22.5 18PR
Number of tires:	12
<b>Control configuration</b>	
ABS anti-lock braking system:	<input checked="" type="checkbox"/>
<b>External Configuration</b>	
Aluminum alloy gas tank:	<input checked="" type="checkbox"/>
<b>Internal Configuration</b>	
Air conditioning adjustment form:	Manual
Reversing image:	<input type="checkbox"/>
Electronic central locking:	<input checked="" type="checkbox"/>
<b>Lighting Configuration</b>	
Daytime running lights:	<input checked="" type="checkbox"/>
<b>Braking</b>	
Front wheel brake:	Drum brake
Rear brake:	Drum brake