

	<b>Sinotruk HOWO Leader 160HP 4X2 4.1m Refrigerated Truck (National VI)(Greenleaf Refrigerated)(ZZ5047XLCH3315F145)</b> <a href="#">+ contrast</a>
<b>Basic Information</b>	
Drive type:	4X2
Wheelbase:	3360mm
Body size:	5.995×2.35×3.425 m
Front overhang/rear overhang:	1.16/1.555m
Rated load:	1.155 tons
Vehicle weight:	3.21 tons
Total mass:	4.495 tons
Front track:	1610mm
Rear track:	1555mm
Maximum speed:	95km/h
Fuel Type:	diesel fuel
<b>Engine parameters</b>	
Engine Brand:	Weichai
Engine Model:	Weichai WP3NQ160E61
Number of cylinders:	4 cylinders
Maximum output power:	118kW
Maximum horsepower:	160 HP
Displacement:	2.97L
Emission standards:	National VI
Fuel Type:	diesel fuel
Rated speed:	3000rpm
Engine Type:	In-line, direct injection, water-cooled, four-stroke, supercharged and intercooled, electronically controlled high-pressure common rail
Maximum Torque:	480N·m
<b>Cargo box parameters</b>	
Cargo box dimensions:	4.1×2.3×2.05m
Length of cargo box:	4.1 m
Cargo box width:	2.3 m
Cargo box height:	2.05m
<b>Upload parameters</b>	
Vehicle announcement:	ZZ5047XLCH3315F145
Vehicle type:	Refrigerated Truck
Top brand:	Sinotruk HOWO light truck
Vehicle Origin:	Zhangqiu, Shandong
<b>Cab parameters</b>	
Cab:	Single row
<b>Gearbox parameters</b>	
Gearbox Model:	6-speed gearbox
Number of gears:	6 gears
Gear shifting mode:	Manual
<b>tank</b>	
Fuel tank material:	plastic
Fuel tank capacity:	120L
<b>Chassis parameters</b>	
Chassis Brand:	Sinotruk HOWO light truck
Chassis series:	Commander
Chassis Model:	ZZ1047H3315F145Z
Speed ratio:	4.875
Number of springs:	8/9+6
<b>tire</b>	
Number of tires:	6
Tire specifications:	7.50R16LT 8PR