

	Wuling Rongguang 2.3T 2.845m single-row pure electric van truck (LZW5028XXYLEVA6EAU) 41.5kWh +contrast >	Wuling Rongguang small truck basic model 2.4T 2.71m single row pure electric flatbed small truck (LZW1029EVHEAU) 41.5kWh < +contrast >	Wuling Rongguang small truck basic model 2.4T 2.71m single row pure electric plate small truck (LZW1029EVA6EAU) 41.5kWh < +contrast >	Wuling Rongguang Light Truck Comfort Type 2.4T 2.71m Single-row Pure Electric Barrier Light Truck (LZW1029EVHEAU) 41.5kWh < +contrast >
Basic Information				
Announcement Model:	LZW5028XXYLEVA6EAU	LZW1029EVHEAU	LZW1029EVA6EAU	LZW1029EVHEAU
type:	Box truck	Truck	Truck	Truck
Wheelbase:	3050mm	3050mm	3050mm	3050mm
Box length level:	2.8 m	2.7 m	2.7 m	2.7 m
Body length:	4.98 m	4.535m	4.535m	4.535m
Body width:	1.595/1.64m	1.595m	1.595m	1.595m
Ride height:	2.345 m	1.87 m	1.87 m	1.87 m
Total mass:	2.3 tons	2.4 tons	2.4 tons	2.4 tons
Rated load:	0.702 tons	0.97 tons	0.97 tons	0.97 tons
Vehicle weight:	1.468 tons	1.3 tons	1.3 tons	1.3 tons
Maximum speed:	100km/h	100km/h	100km/h	100km/h
Factory standard battery life:	232km	296km	296km	296km
Tonnage level:	Micro Card	Micro Card	Micro Card	Micro Card
Origin:	Qingdao, Shandong	Qingdao	Qingdao	Qingdao
Remark:	Optional side door/non-side door cargo box.			Standard: reversing radar, silver-white front and rear bumpers; Optional: air conditioning
Motor				
Motor Brand:	Tongyu	Huichuan	Tongyu	Huichuan
Motor Model:	TZ185XSTY3202	TZ180XSIN102	TZ185XSTY3202	TZ180XSIN102
Motor type:		Permanent magnet synchronous motor	Permanent magnet synchronous motor	Permanent magnet synchronous motor
Power Rating:	30kW	30kW	30kW	30kW
Peak Power:	60kW	60kW	60kW	60kW
Peak Torque:		220N·m	220N·m	220N·m
Fuel Type:	Pure Electric	Pure Electric	Pure Electric	Pure Electric
Cargo box parameters				
Cargo box form:	Box	Fence type	Fence type	Fence type
Length of cargo box:	2.845 m	2.71 m	2.71 m	2.71 m
Cargo box width:	1.525m	1.52m	1.52m	1.52m
Cargo box height:	1.53m	0.32m	0.32m	0.32m
Cab parameters				
Number of passengers allowed:	2 people	2 people	2 people	2 people
Number of Seat Rows:	Single row	Single row	Single row	Single row
Chassis parameters				
Permissible load on front axle:	750kg	850kg	850kg	850kg
Rear Axle Description:		Longitudinal leaf spring	Longitudinal leaf spring	Longitudinal leaf spring
Permissible load on rear axle:	1550kg	1550kg	1550kg	1550kg
tire				
Tire specifications:	175/75R14C 99/98	175/75R14C 99/98	175/75R14C 99/98	175/75R14C 99/98
Number of tires:	4	4	4	4
Battery				
Battery Brand:	Penghui	Penghui	Penghui	Penghui
Battery Type:	Lithium Iron Phosphate	Lithium Iron Phosphate	Lithium Iron Phosphate	Lithium Iron Phosphate
Battery capacity:	41.5kWh	41.5kWh	41.5kWh	41.5kWh
Charging method:		DC fast charging	DC fast charging	DC fast charging
Control configuration				
ABS anti-lock braking system:	●	●	●	●
Power steering:	Electric power assist	Mechanical assistance	Mechanical assistance	Mechanical assistance
Internal Configuration				
Air conditioning adjustment for m:	Optional manual		Manual	
Power windows:	○			●
Remote control key:	○			●
Electronic central locking:	○			●
Electronic central locking:	○			●
Lighting Configuration				
Headlight height adjustable:			●	
Braking				
Front wheel brake:	Disc	Disc	Disc	Disc
Rear brake:	Drum	Drum	Drum	Drum